

# MATERIALS SAFETY DATA SHEET

SUPER-KRETE INTERNATIONAL, INC.  
1290 N. Johnson #101  
El Cajon, CA 92020  
Toll Free: 800-995-1716/619-401-8282  
FAX: 619-401-8288      www.super-krete.com

EMERGENCY TELEPHONE NUMBER: (800) 995-1716

County of San Diego Hazardous Materials Division: (619) 236-2222  
Cal-Osha: (619) 279-3771  
Date Prepared: November 8, 2000

## SECTION I – PRODUCT IDENTIFICATION

Product Code: S-9500 Color Stain, Various Colors  
Trade Name: Super-Krete® Synthetic Resin Emulsion  
C.A.S. Number: Mixture  
Product Class: Self-cross linking Acrylic Latex

## SECTION II – HAZARDOUS INGREDIENTS

This material contains no ingredients required to be listed by OSHA per 29 CFR 1910.1200.

## SECTION III – PHYSICAL DATA

Boiling Point: 212 Degrees F.  
Vapor Density: Heavier than air  
Evaporation Rate: Slower than n-Butyl Acetate  
Specific Gravity: 1.060  
Parent Volatiles: 54-56 by weight  
Appearance: White liquid, slight acrylic odor

## SECTION IV – FIRE & EXPLOSION HAZARD DATA

Flammability Class: 3B  
Flash Point: 212 Degrees F. LEL: N/A  
Extinguishing Media: Water, carbon dioxide, or dry chemical  
Special Firefighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus.  
Unusual Fire & Explosion Hazards: This material may generate formaldehyde when heated.

## SECTION V – HEALTH HAZARD DATA

Permissible Exposure Level: Not established. However, this material may release formaldehyde fumes when heated or cured.

The ACGIH TLV for formaldehyde is currently set at 1 ppm for an 8 hour TWA and a 2 ppm STEL for a 15 minute period.

The OSHA PEL for formaldehyde is currently set at 3 ppm for an 8 hour TWA and a 5 ppm acceptable ceiling concentration.

Effects of Overexposure: SKIN: This material may cause skin irritation or rash upon prolonged or repeated contact.

Inhalation: Excessive exposure to vapors or spray mists can cause irritation of eyes, nose and throat.

Eyes: This material may be an eye irritant.

Carcinogenicity: Formaldehyde is listed as a potential carcinogen by the National Toxicology Program (NTP) and by the International Agency for Research on Cancer (IARC).

First Aid: Skin: Wash with soap and water.  
Eyes: Flush with large quantities of water for 15 minutes and seek medical attention.  
Ingestion: If ingested, call a physician at once.

Primary Route of Entry: Inhalation of vapors (especially if sprayed or heated).

#### **SECTION VI – REACTIVITY DATA**

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility: None Known

Conditions to Avoid: Keep from freezing

Hazardous Decomposition Products: Under severe thermal degradation, low molecular weight organic compounds will be formed.

#### **SECTION VII – SPILL OR LEAK PROCEDURES**

With small spills or leaks use absorbent material such as a sawdust, vermiculite or sand. Larger spills dilute with large amounts of water, before flushing to a sewer or drain according to local, provincial or federal regulations.

#### **SECTION VIII – SPECIAL INFORMATION**

Keep container closed when not in use. Store away from heat and do not freeze. Keep out of reach of children.

The information contained herein is based on data considered accurate. However, no warrant, whether express or implied is made. SUPER-KRETE International, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.