

# S-8402 Paint Chips™

TECHNICAL DATA SHEET

## DESCRIPTION

Super-Krete® Paint Chips™ are integrally colored, randomly sized and shaped flakes that are made from resins and other materials. Paint Chips are effective in enhancing the appearance of seamless floors or hiding imperfections on coated floors, walls and for creating various decorative effects. Paint chips may be used to give the illusion of terrazzo. Refer to Super-Krete Spec. S-8401 Paint Chip Industrial Flooring System.

## USES

Decorative Concrete Surfaces  
Traffic Areas  
Garage Floors  
Commercial Shops

Warehouses  
Automotive Industry  
Decorative Walls  
Solvent / Water-based Sealers

Interior / Exterior Use  
Schools  
Shopping Centers



## ADVANTAGES

Decorative  
Many Color Combinations  
Slip Resistant

Added Texture  
Flexible  
Hides Imperfections

11 Color Selections  
Resistant to UV Rays  
Simple Installation

## CSI RELATED SECTIONS

03 35 00 - Concrete Finishing

09 90 00 - Painting and Coating

09 93 00 - Staining and Transparent Finishing

09 96 00 - High Performance Coatings

32 00 00 - Exterior Improvements

## APPLICATION

Apply two coats of Supra-Seal™ or Supra Seal II solvent-based sealers at a rate of 300-500 sf per gallon with a 1/4" nap non-shed roller per Super-Krete specifications. Wait 2-4 hours before applying the second coat to allow for gassing. Broadcast Paint Chips directly on to the wet second coat of sealer at the desired rate to achieve the desired effect or look. After Paint Chips have been broadcast and the second coat is dry, use a scraper to remove any loose paint chips. Remove all excess Paint Chips and broken pieces with a leaf blower or broom. Wait 4-8 hours and apply a light coat of Supra Seal sealer. Wait 4 hours, but no more than 8 hours and finish with the final coat of sealer. Allow 72 hours to dry before allowing vehicular traffic. Refer to the Technical Data Sheet for the Super-Krete sealer in use for proper application instructions.

## Coverage Rate

Approximately 50 sf / lb.

*\*Coverage shown is for a medium broadcast. Coverage rate may vary. Actual coverage will vary per heavy or light broadcast.*

## Shelf Life

5 years when properly stored.

## Storage

Store in a cool, dry place.

## Tools Required

Floor scraper  
Leaf blower  
Broom

## Packaging

Available per pound. 11 standard colors available.

*\* There may be a slight variation in the Paint Chip sizes and shapes due to the manufacturing process. The average size of chips is 1/4". Some dust may be present within each unit.*

**Appearance** Opaque solid

**Odor** None

## CAUTION

Keep away from children. Do not take internally. Always use safety gloves, appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist both indoors and outdoors. If ingested, seek medical attention immediately.

## LIMITATIONS

Super-Krete products are to be applied only when surface temperatures are above 55° F and rising and not to exceed 100° F. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze. Each Super-Krete product acts as an inherent part of a proven system. Super-Krete products are professional, contractor grade products. Training in the use of these products is available. Consult Super-Krete for information and assistance locating approved contractors in your area or for training class dates.

**NOTE:** Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

