

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING TRADE NAME: CEM-SEAL
4565 W. WATKINS ST. **COLOR:** WHITE AND TINTS

PHOENIX, AZ 85043 MAIN USE: SPECIALTY FLOOR COATING

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION: HAZARDOUS **CARCINOGENICITY:** CATEGORY 2

GHS LABEL ELEMENTS HAZARD PICTOGRAMS





SIGNAL WORD: WARNING!

HAZARD STATEMENTS:

H351: SUSPECTED OF CAUSING CANCER

PRECAUTIONARY STATEMENTS:

PREVENTION

P202: DO NOT HANDLE UNTIL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD

RESPONSE

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

OTHER HAZARDSNO DATA AVAILABLE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	Wt. %	CAS Number
TRIMETHYLPENTANEDIOL MONOISOBUTYRATE	1.0-5.0	025265-77-4
TITANIUM DIOXIDE	0-20	013463-67-7
IRON (III) OXIDE	0-10	001309-37-1
CARBON BLACK	0-10	001333-86-4

CEM-SEAL PIGMENTED Page 2 of 5

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE AFFECTED PERSON FROM AREA. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. IF BREATHING REMAINS OR BECOMES LABORED, SEEK MEDICAL ATTENTION.

INGESTION: GIVE 3 – 4 GLASSES OF MILK OR WATER. **DO NOT INDUCE VOMITING.** SEEK MEDICAL ATTENTION.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: NA

CONDITIONS OF FLAMMABILITY: NA

OSHA CLASS: NONE SHOWN

AUTO IGNITION TEMP.: NA

FLAMMABLE LIMITS: <u>LEL:</u> NE <u>UEL:</u> NE <u>SENSITIVITY TO IMPACT: NONE</u>

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: WATER, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: POLYMER FILM CAN BURN, MATERIAL CAN SPLATTER ABOVE 100°C

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.

STORAGE: STORE BETWEEN 40°F AND 100°F PROTECTED FROM FROST AND DIRECT SUNLIGHT.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS (ppm)				
INGREDIENTS (CAS)	OSI	IA	ACGIH	OTHER
	TWA	STEL	TWA STEL	
025265-77-4	NE	NE	NE NE	
013463-67-7	10mg/m^3	ND	10mg/m^3 ND	(SEE NOTE 1)
001309-37-1	5mg/m^3	ND	5mg/m^3 ND	(SEE NOTE 1)
001333-86-4	3.5mg/m^3	ND	$3.5 \mathrm{mg/m^3}$ ND	(SEE NOTE 1)

<u>LEGEND</u>: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

CEM-SEAL PIGMENTED Page 3 of 5

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION CON'T.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >100°C (>212° F) **SPECIFIC GRAVITY**: 1.2-1.3

VAPOR PRESSURE: ND

VAPOR DENSITY: >1

(AIR = 1)

MELTING POINT: ND

EVAPORATION RATE: <1
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: DILUTABLE pH: 8.0 TO 11.5

COEFFICIENT of WATER/OIL DISTRIBUTION: ND ODOR THRESHOLD: ND

APPEARANCE AND ODOR: PIGMENTED LIQUID, MILD ODOR

% VOLATILES BY VOLUME: 62% %SOLIDS BY WEIGHT: 50%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES INCOMPATIBILITY (MATERIAL TO AVOID): NONE KNOWN HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

CONDITIONS TO AVOID: KEEP FROM FREEZING

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE – MAY CAUSE MILD IRRITATION WITH BLURRED VISION. CHRONIC– $\ensuremath{\mathsf{ND}}$

SKIN CONTACT:

ACUTE – TRANSIENT IRRITATION AND REDNESS. CHRONIC – ND

SKIN ABSORPTION:

ACUTE – ND CHRONIC – ND **CEM-SEAL PIGMENTED** Page 4 of 5

SECTION 11: TOXICOLOGICAL INFORMATION

INHALATION:

ACUTE - INHALATION OF MISTS MAY CAUSE MILD RESPIRATORY TRACT IRRITATION. CHRONIC - EXCESSIVE EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION OF EYES, NOSE AND THROAT.

INGESTION:

ACUTE - MAY CAUSE MILD IRRITATION OF GASTRO-INTESTINAL TRACT CHRONIC - ND

CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN.

OVEREXPOSURE EFFECTS: IRRITATION

IRRITANCY: YES - REVERSIBLE

SENSITIZER: NO

ACUTE TOXICITY

ACUTE ORAL TOXICITY- COMPONENTS

TRIMETHYLPENTANEDIOL MONOISOBUTYRATE LD50: 3400 mg/kg SPECIES: RAT

ACUTE INHALATION TOXICITY- COMPONENTS OECD TEST GUIDLINE 403

TRIMETHYLPENTANEDIOL MONOISOBUTYRATE LC50(4 HR): 4.224 mg/l SPECIES: RAT

ACUTE DERMAL TOXICITY- COMPONENTS

ND

SKIN CORROSION/IRRITATION

RABBIT, NON-IRRITANT

SERIOUS EYE DAMAGE/EYE IRRITATION

RABBIT, NON-IRRITANT

CARCINOGENIC DATA: NTP: NONE OSHA: NONE IARC: 2B TERATOGENICITY: NO MUTAGENICITY: NO

EMBRYOTOXICITY: NO SYNERGISTIC MATERIAL: NO

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

ACUTE TOXICITY TO FISH

ACUTE TOXICITY TO AQUATIC INVERTEBRATES

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS

ND

TOXICITY TO BACTERIA

ND

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: READILY BIODEGRADABLE (BY OECD CRITERIA)

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: NOT BIOACCUMULATIVE

MOBILITY IN SOIL: ND

SAFETY DATA SHEET

CEM-SEAL PIGMENTED Page 5 of 5

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: NOT A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: NOT REGULATED HAZARD CLASS: NA

UN NUMBER: NA PACKAGING GROUP: NA

DOT PRODUCT RQ LBS (KGS): NA HAZARD LABEL: NA

HAZARD PLACARD NA

ADDITIONAL INFORMATION: NONE

SECTION 15: REGULATORY INFORMATION

MATERIAL VOC = 41 gram / liter

COATING VOC = 97 gram/liter

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: SLIGHT HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: NONE ABOVE de Minimus LEVELS

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: CAS # 013463-67-7, CAS # 001333-86-4

SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: JUNE 18, 2015 REVISION DATE: PREPARED BY: J.W. ESSIG

HAZARD RATING

HMIS: HEALTH 1 FLAMMABILITY 0 REACTIVITY 0

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

STEL: SHORT TERM EXPOSURE LIMIT TWA: TIME WEIGHTED AVERAGE PEL: PERMISSIBLE EXPOSURE LIMIT TLV: THRESHOLD LIMIT VALUE

NA: NOT APPLICABLE NE: NOT ESTABLISHED

ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.