# SAFETY DATA SHEET



S-8700 Interior Floor Finish Wax

SDS Number : S-8700

Revision Date: 11/11/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION:

Product Name: S-8700 Interior Floor Finish Wax Product Code: S-8700 Product Use: Institutional Floor Polish Synonyms: Waterborne Acrylic Emulsion Floor Finish, Chemical Formula: Mixture of substances listed below with nonhazardous additions Restrictions: Institutional, Commercial, Retail and Industrial Floor Care Use Only



Manufacturer:

Arizona Polymer Flooring, Inc. 4565 W. WATKINS ST. PHOENIX, AZ 85043

www.super-krete.com

Emergency contact: Chemtrec 800.424.9300

## 2. HAZARD IDENTIFICATION:

#### GHS CLASSIFICATION:

| <u>HEALTH</u>   | <b>ENVIRONMENTAL</b>                                       | <u>PHYSICAL</u> |  |
|---|--|-----------------|--|
| This product is non-hazardous<br>according to OSHA 29CFR<br>1910.1200   | Acute Toxicity: None Known<br>Chronic Toxicity: None Known | None            |  |
| <u>GHS Pictogram</u>  | <u>Signal Word:</u>  |                 |  |
| None  | None   |                 |  |
|   | Hazard Statements  |                 |  |
| May cause mild skin and eye irritation  |  |                 |  |
| <u>Precautionary</u> <u>Statements</u><br>Wear protective gloves/protective clothing/eye protection/face protection.  |  |                 |  |
| <ul> <li>IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do.</li> <li>Continue rinsing. If irritation occurs and persists, get medical attention.</li> <li>IF ON SKIN: Wash with soap and water. If irritation occurs and persists, get medical attention.</li> <li>IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if you feel unwell.</li> <li>IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical attention if you feel unwell.</li> </ul> |  |                 |  |
| Store in a closed container.  |  |                 |  |
| Dispose of contents/container in accordance with local regulation.  |  |                 |  |

### **3. COMPOSITION/INFORMATION ON INGREDIENTS:**

| INGREDIENT  | CAS NO.  | PERCENT | HAZARDOUS |
|---|----------|---------|-----------|
| DIETHYLENE GLYCOL MONOETHYL ETHER                                 | 111-90-0 | 4-5%    | YES       |
| ETHYLENE GLYCOL   | 107-21-1 | 1-2%    | YES       |
| TRIBUTOXYETHYL PHOSPHATE  | 78-51-3  | 1-3%    | YES       |
|   |          |         |           |
| Exact Percentages are being withheld as trade secret information. |          |         |           |

# S-8700 Interior Floor Finish Wax

### 4. FIRST-AID MEASURES:

Eye Contact: Rinse with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. If irritation occurs and persists, get medical attention.
 Skin Contact: Wash with soap and water. If irritation occurs and persists, get medical attention.
 Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if you feel unwell.
 Indestion: Remove how the position of the presence of the prese

Ingestion: Rinse mouth. Do NOT induce vomiting. Get medical attention if you feel unwell.

### **5. FIRE-FIGHTING MEASURES:**

*Fire Extinguishing media:* Use water spray dry chemical, carbon dioxide or regular foam. Move containers away from fire area if can be done without risk.

Hazards during fire-fighting:

Containers may rupture when exposed to extreme heat.

#### Protective equipment for fire-fighting:

Wear NFPA-approved self-contained breathing apparatus, helmet, hood, boots and gloves.

# 6. ACCIDENTAL RELEASE MEASURES:

#### Personal precautions:

Use recommended personal protective clothing and equipment. To prevent slipping, do not walk through spilled material.

#### Environmental precautions:

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off of work area, and material should be absorbed, collected and disposed of in accordance with regulations. Keep product from entering storm drains. Consult local and federal guidelines for proper disposal of these materials.

#### Cleanup:

- For small amounts of released material: Mop or vacuum up then transfer to suitable container for disposal. - For large amounts of released material: Dike around spilled material to contain. Spilled material may be mopped or vacuumed up, then transferred to plastic containers for disposal.

#### 7. HANDLING and STORAGE:

#### <u>Handling:</u>

**General advice** - No specific measures are necessary provided product and recommended protective clothing/equipment are used correctly. Do not mix with other chemicals. This is a commercial product, not intended for home use. Keep out of reach of children.

#### Storage:

**General advice** - Protect against physical damage. Store in tightly closed containers in a cool, well ventilated area. Do not allow product to freeze.

## Shelf Life:

12 months

# S-8700 Interior Floor Finish Wax

# 8. EXPOSURE CONTROLS and PERSONAL PROTECTION:

Advice on system design:

Provide local exhaust ventilation to control vapors for published exposure limits.

### Personal protective equipment (HMIS rating 'B'):

**Eye protection**: Wear safety glasses with side shields or safety goggles to prevent exposure or full face shield if splash hazard exists.

Skin protection: Chemical-resistant gloves. Wear appropriate protective clothing to prevent possible skin contact.

**Respiratory protection**: Use proper NIOSH-OSHA respirator if exposure limits are exceeded or ventilation is inadequate. **General safety and hygiene measures**: Exercise stringent hygiene practices to minimize exposure.

If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking

or smoking.

#### Other protective measures:

Nearby running water on the job site is necessary, should an accident occur.

Exposure Guidelines:

| ACGIH TLV: | 20 ppm (107-21-1), Not Established (111-90-0)          |
|------------|--|
| STEL:      | Not Established (107-21-1), Not Established (111-90-0) |
| OSHA PEL:  | Not Established (107-21-1), Not Established (111-90-0) |

## 9. PHYSICAL and CHEMICAL PROPERTIES:

| Appearance:                 | White Liquid             | Flash Point:                     | > 200°F                  |
|-----------------------------|--------------------------|----------------------------------|--------------------------|
| Odor:                       | Sweet                    | Upper/Lower Flammability Limits: | No information available |
| pH value:                   | 8.5 +/- 0.2              | Relative Density (water):        | 1.02                     |
| Specific gravity:           | 1.02 (H2O = 1)           | Auto-Ignition Temperature:       | No information available |
| Solidification temperature: | No information available | Decomposition temperature:       | No information available |
| Freezing/Melting point:     | 32 °F (0 °C)             | Partition Coefficient            | No information available |
| Boiling point:              | 212°F (100 °C)           | Odor Threshold                   | No information available |
| Vapor density:              | No information available | Viscosity:                       | < 10 cps.                |
| Vapor pressure:             | No information available | Partition Coefficient            | No information available |
| Evaporation Rate:           | No information available | Solubility in water:             | Miscible                 |
| Regulatory VOC:             | < 1% by weight           |                                  |                          |

## **10. STABILITY and REACTIVITY:**

Conditions to avoid: Freezing. Excessive heat or flame.
 Substances to avoid: Strong oxidizing agents, acids and bases.
 Hazardous reactions: Product is chemically stable under normal conditions of use and storage.
 Decomposition or By-products: In fire conditions: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>).

# **11. TOXICOLOGY INFORMATION:**

#### Acute Toxicity (Symptoms):

Oral: Ingestion may cause nausea, vomiting, and diarrhea. Eye irritation: Mild irritation, redness and tearing. Skin irritation: Mild irritation and redness. Inhalation: May cause minor irritation to the respiratory tract. Sensitization: Skin: N/A. Respiratory: N/A

#### Chronic Toxicity:

Other information: No carcinogenic substances as defined by IARC, NTP and/or OSHA.

# S-8700 Interior Floor Finish Wax

# **12. ECOLOGICAL INFORMATION:**

#### **Biodegradation:**

Test method: Unspecified Analysis method: Unspecified Degree of elimination: Not Established

#### Environmental toxicity:

Acute and prolonged toxicity to fish: Not Established Toxicity to microorganisms: Not Established Other ecotoxicological advice: Not Established

## **13. DISPOSAL CONSIDERATIONS:**

*Waste disposal of substance:* Dispose of in accordance with all Federal, State and Local regulations when storing and disposing of substances. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA (EPA regulations for hazardous waste).

Container disposal: Dispose of in a licensed facility in accordance with local regulations.

#### RCRA:

Unspecified.

## **14. TRANSPORTATION INFORMATION:**

DOT: Proper Shipping Name: WAX, LIQUID (NON-HAZARDOUS)

#### **15. REGULATORY INFORMATION:**

| Federal Regulations         | 5:  |
|-----------------------------|---|
| <b>Registration status:</b> |   |
| TSCA, US:                   | All components are listed or exempt.  |
| SARA hazard catego          | ory (EPCRA 311/312): Acute health hazard  |
| SARA TITLE III, SECT        | TON 313:  |
| CAS Number:                 | Chemical Name:  |
| 111-90-0                    | Diethylene Glycol Monoethyl Ether   |
| 107-21-1                    | Ethylene Glycol   |
| State Regulations:          |   |
| Chemicals known to          | the State of California to cause cancer, birth defects or other reproductive harm |
|                             |   |

CAS Number:Chemical Name:107-21-1Ethylene Glycol (Ingested)

# SAFETY DATA SHEET

| S-8700 Interior Floor<br>Finish Wax |   | SDS Number : S-8700        |                     | Revision Date: 11/11/2015                     |
|-------------------------------------|---|----------------------------|---------------------|---|
| 16. OTHER INFORM                    | ATION:  |                            |                     |   |
| NFPA Rating:                        |   |                            |                     |   |
| Health: 1                           | Fire: 0   | Reactivity: 0              | Special H           | lazard: none                                  |
| HMIS III Ratin                      | ng:   |                            |                     |   |
| Health: 1                           | Flammability: 0   | Physical Hazard: 0         |                     |   |
| Personal Prot                       | ection: B (safety glasses                               | with side shields and chem | ical-resistant gl   | oves)   |
|                                     | ating systems use a numbe<br>azard while a value of fou |                            | to 4 to indicate th | e degree of hazard. A value of zero means the |
| NFPA Rating                         |   |                            |                     |   |
|                                     | HMIS Rat  | ing                        |                     |   |

HMIS Rating HEALTH 1 FLAMMABILITY 0 PHYSICAL HAZARD 0 PERSONAL PROTECTION B

**Notice:** The information provided is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

**Warranty:** This is a proprietary Super-Krete Products, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact Super-Krete Products with any questions regarding this policy.