

MIXING AND APPLICATION

Add water to S-9350 Glo-Kote to achieve a plaster-like consistency. The appropriate amount of water is necessary for S-9350 Glo-Kote to maintain the desired thickness. Do not over-dilute the product. Lightly mist the surface with clean water and apply S-9350 Glo-Kote mixture at a minimum 1/8" thickness using a cement trowel, screed rake or squeegee. Squeegees are recommended when applying large amounts at one time, but multiple applications will be required to obtain a minimum 1/8" thickness. For best results, first apply one application of S-9302 Bond-Kote® White as a base coat and allow to dry thoroughly.

S-9350 Glo-Kote must be applied in areas where there will be direct or indirect sunlight. The energizing of the glow is maximized by direct sunlight. Access to direct sunlight will yield a longer lasting and brighter glow. S-9350 Glo-Kote will reach its maximum charge rate from its light source in 2 hours (a light sub-surface will increase the glowing effect).

CURING TIME AND SEALING

Allow S-9350 Glo-Kote to cure a minimum of 24 hours in direct sunlight before sealing. Arizona Polymer Flooring recommends sealing all S-9350 Glo-Kote for wear and ease of maintenance. To determine the most appropriate sealer for your project, refer to the **Super-Krete Products Sealer Selection Guide**.

GENERAL INFORMATION

S-9350 Glo-Kote is ready-mixed and only requires the addition of water when mixing. This product requires no primer, bonding agents or cementitious underlayments to ensure a bond. S-9350 Glo-Kote cannot be removed from the concrete substrate once cured, without removing the substrate that it is attached to. This product is a high-strength product that is very resilient and durable.

Coverage Rates

5 sf at 1/8" (1 sf per pound)

**Coverage rates will vary, this is an approximation only. Actual coverage will vary due to substrate conditions, weather, surface porosity and method of application.*

Shelf Life 5 Years when properly stored.
Unopened and sealed

Storage Store in a cool, dry place.
Keep from moisture.

Packaging 5 lb. pail / 50 lb. pail
**(For volume purchasing, please call for pricing)*

Appearance White powdered form

Cure Time 24 hours

Odor None

Specific Gravity 3.15

**Percent Volatiles
by Volume** 0

Tools Required

3 gal. water sprayers
1/2" drill with mixing paddle attachment
5 gallon pails / 55 gallon drum / Plaster mixer
Trowel(s)

CAUTION

Keep away from children. Do not take internally. Always use safety gloves, appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist both indoors and outdoors. If ingested, seek medical attention immediately.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc
4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921
623.435.2277 Tel. / 623.435.8585 Fax
www.super-krete.com

4PUF™ 032417



